



## Aceite para Motor NGEO Low ASH FORMULA MEJORADA NGEO Low ASH Engine Oil IMPROVED FORMULA

### ACEITE PARA MOTOR NGEO LOW ASH FORMULADA MEJORADA



**Mecha Tool® NGEO LOW ASH FORMULA MEJORADA** es un aceite lubricante con un bajo contenido de cenizas sulfatadas. Este lubricante cumple con CUMMINS L10 & M11. Su fórmula balanceada de dispersantes e inhibidores provee control de depósitos y protección contra desgastes, la oxidación y la nitración del aceite. Contiene un componente anti-fricción que lo hace especial en rendimiento y protección mejorando significativamente su capacidad antidesgaste y habilita el motor a trabajar a menos temperatura, así mismo consume menos combustible.

Servicio API: CF

#### BENEFICIOS:

- Alto control de las altas temperaturas de operación de las maquinarias.
- Muy baja formación de depósitos de carbón y reducción del desgaste.
- Especialmente diseñado para motores que trabajan con gas natural, o similares.
- Reduce drásticamente la fricción y desgaste en los motores porque contiene un paquete de aditivos anti-desgaste de extrema presión.
- Alarga la vida útil de la maquinaria.
- Ahorra combustible y aumenta la potencia de los motores.

GRADOS: SAE 40, 15W-40.

PRESENTACIÓN: Paila 5 Galones y Tambor de 55 galones.

#### FICHA TÉCNICA MECHA TOOL® LOW ASH FORMULA MEJORADA

Grado SAE	40	15W-40
Producto	LOW ASH	LOW ASH
Gravedad, ASTM D 4052, 'API	27.9	32.3
Punto de Ignición, ASTM D92 (COC), °C	215	225
Viscosidad, ASTM D 445, cSt at 100 °C	13.0	15.5
ASTM D 445, cSt at 40 °C	113.2	113.0
Índice de Viscosidad, ASTM D 2270	109.6	145
Punto de derrame, ASTM D97, °F(°C)	-15	-25
Ceniza Sulfatada, ASTM D 874, % Max	0.45	0.45
TBN (Total Base no., ASTM D2896	5.1	5.1



Made in U.S.A.

[www.mandjsunshine.com](http://www.mandjsunshine.com)



## NGEO Low ASH Engine Oil **IMPROVED FORMULA**

*Aceite para Motor NGEO Low ASH **FORMULA MEJORADA***

### **NGEO LOW ASH ENGINE OIL IMPROVED FORMULA**



**Mecha Tool® NGEO LOW ASH IMPROVED FORMULA** is a lubricating oil with a low sulfated ash content. This lubricant meets CUMMINS L10 & M11. Its balanced formula of dispersants and inhibitors provides deposit control and protection against wear, oxidation and oil nitration. It contains an anti-friction component that makes it special in performance and protection, significantly improving its anti-wear capacity and enables the engine to work at a lower temperature, as well as consuming less fuel.

**API SERVICE: CF**

**BENEFITS:**

- Improved control of the machinery high operating temperatures .
- Lower carbon deposit formation and wear reduction.
- Specially designed for engines that work with natural gas, or similar.
- Dramatically reduces friction and wear on engines because it contains a package of extreme pressure anti-wear additives.
- Extends the equipment life.
- Saves fuel and increases engine power.

**GRADES:** SAE 40, 15W-40.

**PACKAGING:** 5 Gallon Pail and 55 Gallon Drum.

#### **SPECS SHEET MECHA TOOL® NGEO LOW ASH IMPROVED FORMULA**

Grade SAE	40	15W-40
<b>Product</b>	LOW ASH	LOW ASH
Gravity ASTM D 4052, 'API	27.9	32.3
Ignition point ASTM D92 (COC)	215	225
Viscosity ASTM D 445, cSt at 100	13.0	15.5
ASTM D 445, cSt at 40	113.2	113.0
Viscosity Index ASTM D 2270	109.6	145
Spill Point ASTM D97, °F(°C)	-15	-25
Sulfated Ash ASTM D 874, % Max	0.45	0.45
TBN (Total Base no., ASTM D2896	5.1	5.1



Made in U.S.A.

[www.mandjsunshine.com](http://www.mandjsunshine.com)