



Gasoline Engine Semi-Synthetic Motor Oil Aceite Semi-Sintético para Motores a Gasolina

MECHA TOOL SEMI-SYNTHETIC MOTOR OIL

Mecha Tool is the new SEMI-SYNTHETIC and detergent formulas engineered to provide maximum protection in all weather conditions. **Mecha Tool** meets or exceeds all automobile and light duty truck warranty requirements for gasoline and turbocharged engines where API SN, SM, SL and ILSAC GF-5/GF-4 oils are recommended.

Mecha Tool can be used in place of SJ, SH and SG rated oils. Follow manufacturer's recommendations for viscosity grade and API Service Category.

- ° Meets or exceeds API Service SN, SL, SJ, SH and ILSAC GF-5.
- ° Mecha Tool 5W-20 and 5W 30 meet all requirements for RESOURCE CONSERVING performance standards.
- ° Advanced anti-wear formula to help extend engine life.
- ° High detergency action to help prevent formation of sludge, varnish and rust.
- ° Enhances fuel economy and high protection against thermal breakdown.

PACKAGING: 12 Quart Box, 3/5Qts Box, 55 Gallon Drums



TYPICAL PROPERTIES MECHA TOOL GASOLINE MOTOR OIL

SAE Grade	5W-20	5W-30	15W-40
Viscosity cSt at 40°C	48.0	60.5	97.0
cSt at 100°C	8.10	10.0	13.50
Viscosity Index	140	144	145
API Gravity	32.50	32.50	30.0
Pour Point, °F	-33	-33	-22
Pour Point, °C	-36	-36	-30
Flash Point °F/°C	410°F /210°C	430°F /214°C	401°F /205°C
API Service	SN	SN	SN
Resource Conserving (GF-5)	YES	YES	NO



Made in U.S.A.

www.mandjsunshine.com/mecha-tool